

# SAKO SPECIFICATION SAKO

## SAKO 85 VARMINT LAMINATED STAINLESS



SAKO 85 VARMINT LAMINATED STAINLESS has a series of actions which are designated: Short actions Extra Short (XS) and Short (S). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection and integral tapered scope mount rail. Additionally there is a controlled feed on all models to ensure reliable cartridge feed to the chamber on all situations (Pat. pend.).

The MAGAZINE is detachable and it can also be loaded through the ejection port. Magazine release is prevented against accidental release (Pat. pend.).

The single-set TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-stage trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The straight STOCK with wide fore-end is made of brown mattlaquered laminated hardwood. Strong, extended recoil lug screwed on the fore-end.

SAKO 85 VARMINT LAMINATED STAINLESS is available without open sights. Integral rails for the scope mounts are on the top of the receiver.

The totally free-floating, heavy, fluted BARREL is cold hammer-forged of stainless steel. Available also with short barrel with M18x1 thread at the muzzle for muzzle brake or suppressor assembling.

### TECHNICAL DATA

| Action    | caliber     | rate of twist | Overall length                                   |                    |
|-----------|-------------|---------------|--|--------------------|
| <b>XS</b> | 204 Ruger   | 12"           | <b>XS</b>  | 1095 mm (43 1/8")  |
|           | 222 Rem     | 14"           | <b>XS MT</b>                                     | 1005 mm (39 9/16") |
|           | 223 Rem     | 8"            | <b>S</b>   | 1105 mm (43 1/2")  |
|           | 223 Rem     | 12"           | <b>S MT</b>                                      | 1015 mm (40")      |
| <b>S</b>  | 22-250 Rem  | 14"           | <b>Barrel length</b>                             |                    |
|           | 243 Win     | 10"           | <b>XS / S</b>                                    | 600 mm (23 5/8")   |
|           | 260 Rem     | 8"            | <b>XS / S MT</b>                                 | 510 mm (20")       |
|           | 7mm-08 Rem  | 9.5"          | <b>Weight</b>                                    |                    |
|           | 308 Win     | 11"           | <b>XS</b>  | 3.9 kg (8 5/8 lbs) |
|           | 338 Federal | 10"           | <b>XS MT</b>                                     | 3.7 kg (8 1/8 lbs) |
|           |             |               | <b>S</b>   | 4.1 kg (9 lbs)     |
|           |             |               | <b>S MT</b>                                      | 3.9 kg (8 5/8 lbs) |
|           |             |               | <b>Length of pull</b>                            |                    |
|           |             |               | <b>XS / S</b>                                    | 355 mm (14")       |
|           |             |               | <b>Cartridge capacity</b>                        |                    |
|           |             |               | <b>XS</b> 7 rounds (1 in chamber, 6 in magazine) |                    |
|           |             |               | <b>S</b> 6 rounds (1 in chamber, 5 in magazine)  |                    |